UNI-100[®] FAST, THIXOTROPIC RIGID PVC CEMENT



6111	1041 - GRIFFON UNI-100 [®] BOTTLE 500 ML EN/DE <u>Safety data sheet</u> according to 1907/2006/EC, Article 31
F	Printing date 13.01.2012 Version number 6 Revision: 13.01.2012
	1 Identification of the substance/mixture and of the company/undertaking
	. Product identifier
	 Trade name: <u>Griffon Uni 100</u> Relevant identified uses of the substance or mixture and uses advised against Application of the substance / the preparation Adhesive Details of <u>UNI-100®</u> Further information obtainable from: Bison QESH Emergency telephone number: +31 113 235700
	2 Hazards identification
	 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS07
	Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.
_	. Classification according to Directive 67/548/EEC or Directive 1999/45/EC
	Xi; Irritant
	R36/37: Irritating to eyes and respiratory system.
	F; Highly flammable
	 R11: Highly flammable. Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
-	· Label elements
	. Labelling according to EU guidelines: The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
	. Code letter and hazard designation of product: Xi Irritant F Highly flammable
	. Risk phrases: 11 Highly flammable. 36/37 Irritating to eyes and respiratory system.
	 Safety phrases: 9 Keep container in a well-ventilated place. 16 Keep away from sources of ignition - No smoking. 25 Avoid contact with eyes. 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

1

GB



6111041 - GRIFFON UNI-100[®] BOTTLE 500 ML EN/DE

Safety data sheet

Page 2/8

according to 1907/2006/EC, Article 31

Printing date 13.01.2012 Version number 6

Revision: 13.01.2012

Trade name: Griffon Uni 100 (Contd. of page 1) 46 If swallowed, seek medical advice immediately and show this container or label. 61 Avoid release to the environment. Refer to special instructions/safety data sheets. Other hazards . Results of PBT and vPvB assessment . **PBT:** Not applicable. . **vPvB:** Not applicable. 3 Composition/information on ingredients . Chemical characterization: Mixtures . Description: Adhesive . Dangerous components: CAS: 109-99-9 tetrahydrofuran 50-100% EINECS: 203-726-8 🗙 Xi R36/37; 🚺 F R11 R19 🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE З, НЗЗ5 CAS: 108-94-1 cyclohexanone 10-25% EINECS: 203-631-1 🗙 Xn R20 R10 ♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H332 CAS: 78-93-3 methyl ethyl ketone 2.5-10% EINECS: 201-159-0 🗙 Xi R36; 🔥 F R11 R66-67 🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, нзз6 . Additional information: For the wording of the listed risk phrases refer to section 16. 4 First aid measures . Description of first aid measures . After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stable in side position for transportation. . After skin contact: Generally the product does not irritate the skin. After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. . After swallowing: Do not induce vomiting; call for medical help immediately. Information for doctor: . Most important symptoms and effects, both acute and delayed No further relevant information available. . Indication of any immediate medical attention and special treatment needed No further relevant information available. 5 Firefighting measures . Extinguishing media Suitable extinguishing agents: Water haze Alcohol resistant foam Fire-extinguishing powder Carbon dioxide . For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)

2



6111041 - GRIFFON UNI-100[®] BOTTLE 500 ML EN/DE Page 3/8 Safety data sheet according to 1907/2006/EC, Article 31 Revision: 13.01.2012 Printing date 13.01.2012 Version number 6 Trade name: Griffon Uni 100 (Contd. of page 2) . Special hazards arising from the substance or mixture No further relevant information available. . Advice for firefighters . Protective equipment: Mount respiratory protective device. . Additional information Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system. 6 Accidental release measures . Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Environmental precautions: Prevent seepage into sewage system, workpits and cellars. Do not allow to enter sewers/ surface or ground water. . Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. . Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. 7 Handling and storage . Handling: Precautions for safe handling Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. . Conditions for safe storage, including any incompatibilities Storage: . Requirements to be met by storerooms and receptacles: Store in a cool location. . Information about storage in one common storage facility: Not required. . Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles. . Specific end use(s) No further relevant information available. 8 Exposure controls/personal protection . Additional information about design of technical facilities: No further data; see item 7. · Control parameters . Ingredients with limit values that require monitoring at the workplace: 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone WEL () Short-term value: 20 ppm Long-term value: 10 ppm Sk (Contd. on page 4)

GB



6111041 - GRIFFON UNI-100[®] BOTTLE 500 ML EN/DE

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.01.2012 Version number 6

Revision: 13.01.2012

Trade name: Griffon Uni 100

(Contd. of page 3)

Page 4/8

- 78-93-3 methyl ethyl ketone
 WEL () Short-term value: 899 mg/m³, 300 ppm
 Long-term value: 600 mg/m³, 200 ppm
 Sk

 Additional information: The lists valid during the making were used as basis.
 Exposure controls
 Personal protective equipment:
 General protective and hygienic measures:
 The usual precautionary measures are to be adhered to when handling chemicals.
 Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. . Respiratory protection:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Suitable respiratory protective device recommended.
- . Protection of hands: Solvent resistant gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- . Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- . For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: PVC or PE gloves
- . Eye protection:

Tightly sealed goggles

. Body protection: Solvent resistant protective clothing

<u>9 Physical and chemical properties</u>

. Information on basic physical and chemical properties . General Information . Appearance: Form: Fluid Colour: According to product specification . Odour: Characteristic . Odour threshold: Not determined. . pH-value: Not determined. Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 65°C (Contd. on page 5) GB



Trade name: Griffon Uni 100

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.01.2012 Version number 6

Revision: 13.01.2012

Page 5/8

```
(Contd. of page 4)
                                        < 0°C
 . Flash point:
 . Flammability (solid, gaseous):
                                        Not applicable.
                                        230°C
 . Ignition temperature:
 . Decomposition temperature:
                                        Not determined.
 . Self-igniting:
                                        Product is not selfigniting.
 . Danger of explosion:
                                        Product is not explosive. However, formation
                                        of explosive air/vapour mixtures are
                                        possible.
 . Explosion limits:
      Lower:
                                        1.3 Vol %
      Upper:
                                        12.0 Vol %
 . Vapour pressure at 20°C:
                                        200 hPa
 . Density at 20°C:
                                        0.989 g/cm<sup>3</sup>
 . Relative density
                                        Not determined.
 · Vapour density
                                        Not determined.
                                        Not determined.
 . Evaporation rate
 . Solubility in / Miscibility with
                                        Not miscible or difficult to mix.
      water:
 . Segregation coefficient (n-octanol/
   water):
                                        Not determined.
 . Viscosity:
     Dynamic at 20°C:
                                        2500 mPas
      Kinematic:
                                        Not determined.
      Solids content:
                                        20.9 %
 . Other information
                                        No further relevant information available.
10 Stability and reactivity
 · Reactivity
 . Chemical stability
 . Thermal decomposition / conditions to be avoided:
   No decomposition if used according to specifications.
 · Possibility of hazardous reactions No dangerous reactions known.
 . Conditions to avoid No further relevant information available.
 . Incompatible materials: No further relevant information available.
 . Hazardous decomposition products: Danger of forming toxic pyrolysis products.
11 Toxicological information
 . Information on toxicological effects
 . Acute toxicity:
 . Primary irritant effect:
 . on the skin: No irritant effect.
 . on the eye: Irritating effect.
 . Sensitization: No sensitizing effects known.
 . Additional toxicological information:
   The product shows the following dangers according to the calculation method of
   the General EU Classification Guidelines for Preparations as issued in the latest
   version:
   Irritant
                                                                         (Contd. on page 6)
```



5

GB



(Contd. of page 5)

6111041 - GRIFFON UNI-100[®] BOTTLE 500 ML EN/DE

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.01.2012 Version number 6 Revision: 13.01.2012

Trade name: Griffon Uni 100

12 Ecological information

- . Toxicity
- . Aquatic toxicity: No further relevant information available.
- . Persistence and degradability No further relevant information available.
- . Behaviour in environmental systems:
- . Bioaccumulative potential No further relevant information available.
- . Mobility in soil No further relevant information available.
- · Additional ecological information:
- . General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- . Results of PBT and vPvB assessment
- . **PBT:** Not applicable. . **vPvB:** Not applicable.
- . Other adverse effects No further relevant information available.

13 Disposal considerations

- . Waste treatment methods . Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

. Uncleaned packaging:

. Recommendation: Disposal must be made according to official regulations. Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14 Transport information

17		
	UN-Number	
•	ADR, IMDG, IATA	UN1133
•	UN proper shipping name	
	ADR	1133 ADHESIVES, special provision 640H
	IMDG, IATA	ADHESIVES
•	Transport hazard class(es)	
•	ADR	
	*	
	Class	3 (F1) Flammable liquids.
	Label	3
• • •	IMDG, IATA	
	Class	3 Flammable liquids.
	Label	3
	Packing group	
	ADR, IMDG, IATA	III
		(Contd. on page 7)

GB

Page 6/8



6111041 - GRIFFON UNI-100® BOTTLE 500 ML EN/DE

Page 7/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.01.2012 Version number 6 Revision: 13.01.2012

Trade name: Griffon Uni 100			
	Environmental hazards: Marine pollutant: Special precautions for user Danger code (Kemler): EMS Number: Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	(Contd. of page 6) No Warning: Flammable liquids. 33 F-E,S-D Not applicable.	
	Transport/Additional information:		
	ADR Limited quantities (LQ) Transport category Tunnel restriction code	5L 3 D/E	
	IMDG Remarks: UN "Model Regulation":	Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2 UN1133, ADHESIVES, special provision 640H, 3, III	
		04011, 3, 111	
	Regulatory information Safety, health and environmental regula substance or mixture	tions/legislation specific for the	
•	Labelling according to EU guidelines: The product has been classified and mar Ordinance on Hazardous Materials.	ked in accordance with EU Directives /	
•	Code letter and hazard designation of particular termination of particular termination of particular termination of the second s	roduct:	
	Risk phrases: 11 Highly flammable. 36/37 Irritating to eyes and respirator	y system.	
	<pre>Safety phrases: 9 Keep container in a well-ventilated ; 16 Keep away from sources of ignition - 25 Avoid contact with eyes. 26 In case of contact with eyes, rinse medical advice. 46 If swallowed, seek medical advice imm label. 61 Avoid release to the environment. Re sheets.</pre>	No smoking. immediately with plenty of water and seek mediately and show this container or	
	National regulations:		
	Technical instructions (air): Class Share in % NK 50-100		
	Waterhazard class: Water hazard class 1 (Self-assessment): Chemical safety assessment: A Chemical Safety Assessment has not be		



(Contd. of page 7)

6111041 - GRIFFON UNI-100[®] BOTTLE 500 ML EN/DE

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.01.2012 Version number 6 Revision: 13.01.2012

Trade name: Griffon Uni 100

16 Other information

*

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

	nt phrases
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
НЗ19	Causes serious eye irritation.
НЗЗ2	Harmful if inhaled.
НЗЗ5	May cause respiratory irritation.
НЗЗ6	May cause drowsiness or dizziness.
	Flammable.
R11	Highly flammable.
R19	May form explosive peroxides.
R20	Harmful by inhalation.
R36	Irritating to eves.
R36/37	Irritating to eves and respiratory system.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
Contact	ment issuing MSDS: QESH Department t: Reach coördinator compared to the previous version altered.

Page 8/8